

PDC120A/PDC200A

Single Phase DC Injection Set

High accuracy DC current injection device which could be used in DC generating applications in many different fields.

Specification

Input & Output

| Model | PDC120A | PDC200A |
|-------------------------|-----------------|-----------------|
| Output range | 0~120A | 0~200A |
| Accuracy | ±0.1% | ±0.1% |
| Port voltage | 5.0V | 5.0V |
| Max. current load | 120A | 200A |
| Output time | Continuous | Continuous |
| 10%-90% increasing time | 0A-120A 20mS | 0A-200A 20mS |

Binary inputs

2 independent pairs binary inputs, be capable of judging the open/close function; dry contact and compatible with 30V-250V electric potential; automatic recognition of polarity

Binary output

One pair; contact capacity: 250V DC/0.5A, 250V AC/8A

Timer accuracy

±1ms (0.001 ~ 1s), ±0.1% (1 ~ 999.999s)

Display

4.8inch high resolution LCD display screen

Power supply

Single phase 220V 50HZ -10%+20%

Size and Weight

Size: 330mm x250mm x 260mm

Weight: 10kg

Environment Condition

Temperature: 0℃ ~ 40℃

Humidity≤90%non-condensing

Pressure:86kPa~106kPa



PONOVO POWER CO., LTD.

No.139 Jinghai Third Road, BDA, Beijing, China. 100176

Tel : +86 (10) 59089666

Fax : +86 (10) 59089999

www.ponovo.net

info@relaytest.com

support@relaytest.com