



PNA1000 IEC61850 Digital Substation Network Analyzer



PNA1000

IEC61850 Digital Substation Network Analyzer

Product description

PNA1000 is applied in the digital substation for network communications system, communications process and the real time monitoring of different messages.

It analyzes, warns and records the whole process, data and the abnormal incidents that secure the substation working.

- Warn and detect the faults in substation by monitoring network communications process and status.
- It could do 24-hours online monitoring and analyzing of the IEC61850 message communication in the substation.
- Warn and exclude the hidden dangers by monitoring and analyzing the network messages in station level and process level.
- Provide complete data and analysis methods to substation operation, fault device in station and secondary system fault by visual data and abnormal incident's records.

Record and storage capacity: 1100Mb/s
Accuracy: 100%
Frame lost rate: 0%
EMC tests approved by SGC



Features

- **Get hardware time mark by FPGA**

The event time of all messages including SV, GOOSE, MMS and PTP are stamped by a high performance FPGA, with a 50ns timestamp precision. Accurate record and analysis of the realtime process in a substaion can be implemented. More accurate record of the SV jitter from MUs.

- **Mass data compression technique**

The data compression ratio is as high as 4:1 by applying the data compression algorithm. In the same situation, it gets longer data storage and provides complete data object.


- **Pcap format for the recorded files**

The recorded files are Pcap format that does not need to convert and can be shared with the software and device directly.


- **Accuracy**

It guarantees 100% integrity and accuracy, 0% frame lost rate in condition of 1100Mb/s flow access.


No abnormal incidents with frame size 64/128/256/512/1024/1280/1518 and full load of optics.



Front panel



Front panel



Rear panel

Hardware components


- **Management unit**

HMI of the system to manage the analysis and record unit

- **Analysis and record unit**

Access to the process level/ station level of substation, receive all the messages (Process level: SMV, GOOSE, GMRP and PTP, etc; Station level: MMS, TCP/IP, NTP/SNTP, FTP, ARP, ICMG and IGM, etc) from process/ station levels, and analyzer and compress the messages and the communications status in real-time.

Diagram



Specifications

Record unit	
Hardware	Optional
Data access	≥ 1100Mb/s
Power supply	AC : 220V or 110V (only one gear) DC : 220V or 110V (only one gear)
Ethernet port	2 RJ45 Ethernet ports (Gbps and 1000Mbps are available.) 8 pairs of LC ports, supporting 9-2, GOOSE, MMS and PTP messages.
Communication port	1 RJ45 Ethernet port
Synchronization interface	1 IRIG-B port (ST)
Synchronized accuracy	< 700ns
24 hours accuracy	< 130ms
Potential free output	4
Immunity Test	Stand the Radiated electromagnetic field disturbance tests at severity 4 Stand the Electrical fast transient/burst immunity test at severity 4 Stand the burst immunity test at severity 4 Stand the Electrostatic discharge tests at severity 4 Stand the Surge immunity test at severity 4 Stand the Immunity to conducted disturbances induced by radio frequency fields at severity 4 Stand the Power frequency immunity tests at severity 4 Stand the Voltage dips and short interruption with 100ms (200ms for real) at severity 5
Message access capability	100Mb/s / port, complete record data with total flow 1100Mb/s and 0% package loss rate.
Message storage capacity	Based on the number of MU.*
Indication lights	Power, Running, Sync, Recording, Fault

*Note: It is evaluated on single kit. The MU channel number is 22 at 50Hz.

Equivalent MU	Flow	Messages	Storage days
20	20Mb/s	80-100 thousands frame/s	7
32	32Mb/s	130-150 thousands frame/s	4.5
40	40Mb/s	160-200 thousands frame/s	3.5

Optional Function

1	GOOSE Selection in the offline analysis
2	Flow diagram, Display 4 items in 40 with 1 minute. Add a "Save" button to save present view. Use EXCEL file to play back the wave. PS: the flow refresh period is adjustable.
3	Flow peak value set
4	Watch dog: error-close, ok-open
5	SSD and data-read/save in separate disk
6	Set IP: netmask 255.255.0.0
7	Restart
8	Different orders for fault data
9	Save PACP files in different optic Ethernet. 1. Add optic display function in offline analysis, for example, MAC of GOOSE will be displayed in offline analysis 2. Add "Save as..."in the offline analysis
10	PCAP-Comtrade conversion
11	Only one IP (can be set)
12	PCAP file replay
13	COMTRADE file editing
14	COMTRADE file merge

Appendix: Standard Function

Online analysis	Analysis Unit management
	Real time network traffic monitoring and alarm
	Traffic rush alarm (threshold settable)
	Traffic flow diagram, display 4 items within a settable refresh period. The diagram can be saved in Excel file.
	Real time communication monitoring and alarm
	Real time message analysis and alarm
	Alarm history enquiry
	Search record files by alarms
	Search record files by time
	Message record download and analysis
	MU data jitter monitoring and alarms
	Real time SMV waveform monitoring
	Real time Goose status monitoring
	Real time MMS communication monitoring
Offline analysis	SCD information and signals auto matching
	Message analysis
	Abnormal message position locate
	Traffic flow and abnormality statistics
	MU data jitter analysis
	SMV waveform analysis
	SMV vector analysis
	GOOSE single point selection and analysis
	Goose position shift time analysis
	MMS communication analysis
	PTP clock mode analysis
Data analysis	Waveform scaling
	Single channel analysis
	Duplicate channel analysis
	Feeder components analysis
	Transformer components analysis
	Waveform printing

Professional Solution Provider For The Power World

Προфессионаλ Solution Provider For The Power World



PNA1000 Digital
Substation Network Analyzer



PONOVO POWER CO., LTD.

No.139 Jinghai Third Road, BDA,
Beijing, China. 100176
Tel: +86(10)59089666
Fax: +86(10)59089999
www.ponovo.net
info@relaytest.com
support@relaytest.com