



POM2-6143

Protective Relay Test Set

Specifications

Voltage generators

Setting range

4-phase ac(L-N)	4×0~300V
1-phase ac(L-L)	1×0~600V
dc (L-N)	4×±0~300V
dc (L-L)	1×±0~600V

Power

4-phase ac(L-N)	4×75VA typ., at 300V; 4×50VA guar., at 300V
3-phase ac(L-N)	3×100VA typ., at 300V; 3×85VA guar., at 300V
1-phase ac(L-L)	1× 200VA typ., at 600V; 1× 170VA guar., at 600V
dc (L-N)	4×100W at 300 V

Accuracy error	< 0.08 % rd.+0.02 % rg. guar., at 0~300 V < 0.02 % rd.+0.01 % rg. typ., at 0~300 V
-----------------------	---

Ranges	300V
Resolution	10mV
Distortion	< 0.05 % typ., (< 0.1 % guar.)

Current generators

Setting range

6-phase ac(L-N)	6×0~15A
3-phase ac(2L-N)	3×0~30A
1-phase ac(3L-3L)	1×0~30A (10A/phase)
1-phase ac(6L-N)	1×0~90A
dc (L-N)	6×±0~10A
dc (6L-N)	1×±0~60A

Power

6-phase ac(L-N)	6×105VA at 15A
3-phase ac(2L-N)	3×210VA at 30A
1-phase ac(3L-3L)	1×420VA at 30A
dc(L-N)	6×100W at 10A
dc(6L-N)	600W at 60A

Max compliance voltage(L-N)(L-L)

10Vpk/20Vpk

Accuracy error	< 0.08 % rd.+0.02 % rg. guar., at 0~15A < 0.02 % rd.+0.01 % rg. typ., at 0~15A
-----------------------	---

Ranges	15A or 30A
---------------	------------

Resolution	1mA
-------------------	-----

Distortion	< 0.05 % typ., (< 0.1 % guar.)
-------------------	-----------------------------------

General

Frequency

Sine signal	DC, 0.001Hz~1000Hz
Transient signal	DC ~10.0kHz
Accuracy	±0.3ppm
Resolution	0.001Hz

Phase

Angle range	-360°~+360°
Accuracy	<0.05° typ., <0.1° guar. at 50/60Hz
Resolution	±0.001°

Binary inputs

Number	8
Input characteristics	0~400Vdc/ac (peak) with adjustable threshold or potential free
Time resolution	50μs
Max. measuring time	Infinite
Debounce/Deglitch time	0~25ms
Counting function	< 3kHz at pulse width>150μs

Binary outputs, relay

Number	4 (1-4)
Type	Potential free relay contacts, software controlled
Break capacity ac	Vmax: 300Vac /Imax: 8A /Pmax: 2000VA
Break capacity dc	Vmax: 300Vdc /Imax:8A /Pmax: 150W

Binary outputs, semiconductor

Number	4 (5-8)
Type	semiconductor
Break capacity	Vmax: 300Vdc /Imax:0.5A /Pmax: 150W
Update rate	100μs
Imax	0.5A

Auxiliary dc supply

Voltage range	0~300V
Power	88W at 110V, 110W at 220V, 100W at 300V
Accuracy	error < 0.1 % rg. typ. (<0.5 % rg. guar.)

DC voltage measuring inputs

Measuring range	0~±10V
Accuracy	error <0.02% rg. typ. (<0.05% rg. guar.)
Input impedance	100KΩ

DC current measuring inputs

Measuring range	0~±20mA
Accuracy	error<0.02% rg. typ. (<0.05% rg. guar.)
Input impedance	50Ω

Low level outputs

Setting range	12×0~10Vpk
Max. output current	1mA
Accuracy	error< 0.025 % typ. < 0.07 % guar.at 1~10Vpk
Resolution	250μV
Distortion(THD+N)	< 0.05 % typ. (< 0.1 % guar.)
Connection	14 pin combination socket

Power supply

Nominal input voltage	110~240Vac
Permissible input voltage	90~260Vac
Nominal frequency	50/60Hz
Permissible frequency	45~65Hz

Environmental conditions

Operation temperature	0~+50°C
Storage temperature	-25~+70°C
Relative humidity	5~95% non-condensing
EMC(E&I)	EN/IEC 61326-1
Safety	EN/IEC 61010-1/1-12/2-030 EN/IEC 60255-25/27
Others	FCC Part 15:Sub B ECS-001:2006 LVD EU ZEK 01.4 -08/11/11

Others

PC connection	Ethernet,10M/100M
Low level outputs interface (Optional)	Circular connector
GPS/IRIG-B interface	Circular connector
IEC61850 Goose	Ethernet interface (Optional)
Ground Socket(earth)	4mm banana socket
Weight	16kg
Dimensions (W x H x D)	390mm ×287mm×214mm



PONOVO POWER CO., LTD.

No.139 Jinghai Third Road, BDA, Beijing, China. 100176
Tel : +86 (10) 59089666
Fax: +86 (10) 59089999
www.ponovo.net
info@relaytest.com
support@relaytest.com

